

XJY-301-2 Silicone Pressure Sensitive Adhesive

PRODUCT INTRODUCTION

XJY-301-2 Silicone pressure-sensitive adhesive is a colorless transparent viscous liquid. This glue has moderate peeling power, five toxic, environmentally friendly, skin-friendly, and strong anti-aging ability. It can be used for masking paper or PET film and medical tape. It has good adhesion ability.

PRODUCT FEATURES

- Moderate bonding ability, showing good performance on substrates such as PET and textured paper;
- Excellent resistance to chemical corrosion, anti-ultraviolet aging, and weather resistance;
- Non-toxic, environmentally friendly, no irritation or harm to the human body;
- It is easy to peel off, and there is no residual phenomenon after peeling, and it can be used as a protective tape;



PRODUCT PROPERTY

Product Property	
Appearance	Colorless transparent liquid
Solid Content	58-62%
Viscosity	60000-150000mPa.s
Peel Force	400-600 g/inch
Solvent	Ethyl acetate
Temperature Resistance (°C)	220
Feature	Non-toxic, environmentally friendly, harmless to the human body
Typical Application	Environmental protection, medical tape
Curing System	BPO/Bis(2,4-dichlorobenzoyl) peroxide

INSTRUCTIONS FOR USE

- It is recommended to use the catalyst Bis(2,4-dichlorobenzoyl) peroxide, BPO (benzoyl peroxide), and the catalyst usage amount is 2-3%;
- The temperature of the solvent volatilization section is kept below 120°C to ensure the lowest control of catalyst decomposition and complete solvent volatilization, otherwise the tape will produce pores and affect the performance of the adhesive;
- The catalyst preparation concentration is 10%. After preparation, use it as soon as possible, otherwise the solvent will consume the catalyst and affect the catalytic effect;
- During curing, the curing temperature can be appropriately increased to ensure that the catalyst is completely decomposed, otherwise the tape will easily produce white gel-like substances. If BPO is used as the catalyst, the decomposition of the incomplete catalyst will generate a small amount of carbon dioxide gas, forming pores, and affect the performance of the tape;

PACKAGING, STORAGE, TRANSPORTATION

XJY-301-2 can provide 200Kg inner coated iron drum. If you have special requirements, you can negotiate and customize. This product is stored in the original unopened packaging, when the storage temperature is 25C and below, the validity period of this product is 12 months from the production date. If the storage period is exceeded, the product should be re-tested, and it can still be used if it meets the quality requirements.

PRECAUTIONS

- ◆ The PH value of this series of products is near neutral. If you accidentally touch the skin or eyes, please rinse with plenty of water and go to the hospital for treatment;
- ◆ This product has not been tested or stated as suitable for medical or medicinal use;
- ◆ This information does not include the required product safety information, please read the product description before use;